



## MATERIAL SAFETY DATA SHEET

### 1. Product and Company Identification

|                                 |  |  |
|---------------------------------|--|--|
| <b>Product identifier</b>       | <b>CIM 1000 Premix</b>   |  |
| <b>Version #</b>                | 02   |  |
| <b>Issue date</b>               | 05-19-2015   |  |
| <b>Revision date</b>            | 03-09-2017   |  |
| <b>Supersedes date</b>          | 05-19-2015   |  |
| <b>CAS #</b>                    | Mixture  |  |
| <b>Product use</b>              | Waterproofing, chemical containment, secondary containment   |  |
| <b>Manufacturer information</b> | CIM INDUSTRIES INC<br>6900 NELMS STREET<br>HOUSTON, TX 77061<br>United States<br>info@chasecorp.com<br>General Assistance 800 543-3458<br>Chemtrec (US - 24 hrs) 800 424-9300<br>Chemtrec (INTL - 24 hrs) 703-527-3887 |  |
| <b>Supplier</b>                 | Not available.   |  |

### 2. Hazards Identification

|  |  |
|--|--|
| <b>Emergency overview</b>              | <b>WARNING</b><br><br>Combustible liquid. Cancer hazard. Irritating to eyes and skin.<br><br>Mutagen. Prolonged exposure may cause chronic effects.  |
| <b>Potential health effects</b>        |  |
| <b>Routes of exposure</b>              | Inhalation. Ingestion. Skin contact. Eye contact.  |
| <b>Eyes</b>                            | Contact with eyes may cause irritation. Avoid contact with eyes.   |
| <b>Skin</b>                            | Avoid contact with the skin. May cause skin irritation.  |
| <b>Inhalation</b>                      | May cause cancer by inhalation. May cause irritation of respiratory tract. Prolonged inhalation may be harmful. Do not breathe dust/fume/gas/mist/vapors/spray.  |
| <b>Ingestion</b>                       | Irritating. May cause nausea, stomach pain and vomiting. Do not ingest.  |
| <b>Chronic effects</b>                 | Pregnant women or women of child-bearing age should not be exposed to this product. May cause birth defects. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. |
| <b>Signs and symptoms</b>              | Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Symptoms may include redness, edema, drying, defatting and cracking of the skin.  |
| <b>Potential environmental effects</b> | May cause long-term adverse effects in the environment.  |

### 3. Composition / Information on Ingredients

| Components                                  | CAS #      | Percent |
|---|------------|---------|
| Distillates (petroleum), Hydrotreated Light | 64742-47-8 | 5 - 10  |
| Carbon Black                                | 1333-86-4  | 1 - 5   |
| Stoddard Solvent                            | 8052-41-3  | 1 - 5   |

| Components                                    | CAS #      | Percent  |
|---|------------|----------|
| Solvent naphtha (petroleum), medium aliphatic | 64742-88-7 | 0.1 - 1  |
| Other components below reportable levels      |            | 60 - 100 |

#### 4. First Aid Measures

##### First aid procedures

|                     |   |
|---------------------|---|
| <b>Inhalation</b>   | Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.  |
| <b>Skin contact</b> | Remove and isolate contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin.   |
| <b>Eye contact</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention if irritation develops and persists.  |
| <b>Ingestion</b>    | Rinse mouth thoroughly. Never give anything by mouth to a victim who is unconscious or is having convulsions. If ingestion of a large amount does occur, call a poison control center immediately. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. |

##### Notes to physician

In case of shortness of breath, give oxygen. Symptoms may be delayed.

##### General advice

In case of shortness of breath, give oxygen. If you feel unwell, seek medical advice (show the label where possible). Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep victim under observation. Keep victim warm.

#### 5. Fire Fighting Measures

##### Flammable properties

Combustible by WHMIS criteria. Heat may cause the containers to explode.

##### Extinguishing media

**Suitable extinguishing media** Foam. Dry powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

##### Protection of firefighters

**Specific hazards arising from the chemical** During fire, gases hazardous to health may be formed.

**Protective equipment for firefighters** Firefighters should wear full protective clothing including self contained breathing apparatus.

##### Fire fighting equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.

##### Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

##### Explosion data

**Sensitivity to static discharge** Not available.

**Sensitivity to mechanical impact** Not available.

##### Hazardous combustion products

Not available.

## 6. Accidental Release Measures

|                                  |   |
|----------------------------------|---|
| <b>Personal precautions</b>      | Consider initial downwind evacuation for at least 500 meters (1/3 mile). Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the MSDS.   |
| <b>Environmental precautions</b> | Prevent further leakage or spillage if safe to do so. Do not contaminate water.   |
| <b>Methods for containment</b>   | Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Dike the spilled material, where this is possible. Prevent entry into waterways, sewer, basements or confined areas.   |
| <b>Methods for cleaning up</b>   | <p>Extinguish all flames in the vicinity. Should not be released into the environment. Clean up in accordance with all applicable regulations.</p> <p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.</p> <p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. For waste disposal, see section 13 of the MSDS.</p> |
| <b>Other information</b>         | Clean up in accordance with all applicable regulations.   |

## 7. Handling and Storage

|                 |   |
|-----------------|---|
| <b>Handling</b> | Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes. Avoid contact with skin. Avoid prolonged exposure. When using do not eat or drink. Do not use in areas without adequate ventilation. Wear personal protective equipment. Wash thoroughly after handling. Avoid release to the environment.                 |
| <b>Storage</b>  | Do not handle or store near an open flame, heat or other sources of ignition. Keep at temperature not exceeding 49 °C. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a closed container away from incompatible materials. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Use care in handling/storage. Store away from incompatible materials (see Section 10 of the MSDS). |

## 8. Exposure Controls / Personal Protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

| Components   | Type | Value     | Form                |
|--|------|-----------|---------------------|
| Carbon Black (CAS 1333-86-4)                                   | TWA  | 3 mg/m3   | Inhalable fraction. |
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3 | Non-aerosol.        |
| Stoddard Solvent (CAS 8052-41-3)                               | TWA  | 100 ppm   |                     |

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

| Components   | Type | Value     | Form   |
|--|------|-----------|--------|
| Carbon Black (CAS 1333-86-4)                                   | TWA  | 3.5 mg/m3 |        |
| Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)   | TWA  | 200 mg/m3 | Vapor. |
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3 | Vapor. |
| Stoddard Solvent (CAS 8052-41-3)                               | TWA  | 572 mg/m3 |        |
|  |      | 100 ppm   |        |

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

| Components   | Type | Value     | Form         |
|--|------|-----------|--------------|
| Carbon Black (CAS 1333-86-4)                                   | TWA  | 3 mg/m3   | Inhalable    |
| Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)   | TWA  | 200 mg/m3 | Non-aerosol. |
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3 | Non-aerosol. |
| Stoddard Solvent (CAS 8052-41-3)                               | STEL | 580 mg/m3 |              |
|  | TWA  | 290 mg/m3 |              |

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

| Components   | Type | Value     | Form                |
|--|------|-----------|---------------------|
| Carbon Black (CAS 1333-86-4)                                   | TWA  | 3 mg/m3   | Inhalable fraction. |
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3 | Non-aerosol.        |
| Stoddard Solvent (CAS 8052-41-3)                               | TWA  | 100 ppm   |                     |

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

| Components   | Type | Value     | Form         |
|--|------|-----------|--------------|
| Carbon Black (CAS 1333-86-4)                                   | TWA  | 3.5 mg/m3 |              |
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | TWA  | 200 mg/m3 | Non-aerosol. |
| Stoddard Solvent (CAS 8052-41-3)                               | TWA  | 100 ppm   |              |

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

| Components                       | Type | Value     |
|----------------------------------|------|-----------|
| Carbon Black (CAS 1333-86-4)     | TWA  | 3.5 mg/m3 |
| Stoddard Solvent (CAS 8052-41-3) | TWA  | 525 mg/m3 |
|                                  |      | 100 ppm   |

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components                       | Type | Value      |
|----------------------------------|------|------------|
| Carbon Black (CAS 1333-86-4)     | PEL  | 3.5 mg/m3  |
| Stoddard Solvent (CAS 8052-41-3) | PEL  | 2900 mg/m3 |
|                                  |      | 500 ppm    |

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Exposure guidelines**

**Canada - Alberta OELs: Skin designation**

|  |                                   |
|--|-----------------------------------|
| Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)   | Can be absorbed through the skin. |
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | Can be absorbed through the skin. |

**Canada - British Columbia OELs: Skin designation**

|  |                                   |
|--|-----------------------------------|
| Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)   | Can be absorbed through the skin. |
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | Can be absorbed through the skin. |

**Canada - Manitoba OELs: Skin designation**

|  |                                   |
|--|-----------------------------------|
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | Can be absorbed through the skin. |
|--|-----------------------------------|

**Canada - Ontario OELs: Skin designation**

|  |                                   |
|--|-----------------------------------|
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | Can be absorbed through the skin. |
|--|-----------------------------------|

**Canada - Saskatchewan OELs: Skin designation**

|  |                                   |
|--|-----------------------------------|
| Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8) | Can be absorbed through the skin. |
|--|-----------------------------------|

|  |                                   |
|--|-----------------------------------|
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | Can be absorbed through the skin. |
|--|-----------------------------------|

**US ACGIH Threshold Limit Values: Skin designation**

|  |                                   |
|--|-----------------------------------|
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) | Can be absorbed through the skin. |
|--|-----------------------------------|

|                             |  |
|-----------------------------|--|
| <b>Engineering controls</b> | Ensure adequate ventilation, especially in confined areas. Good general ventilation should be used (see CIM IG-9 for additional details). Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |
|-----------------------------|--|

**Personal protective equipment**

|                            |   |
|----------------------------|---|
| <b>Eye/face protection</b> | Wear safety glasses with side shields (or goggles). |
|----------------------------|---|

|                        |  |
|------------------------|--|
| <b>Skin protection</b> | Wear suitable protective clothing. Wear protective gloves. |
|------------------------|--|

|                               |   |
|-------------------------------|---|
| <b>Respiratory protection</b> | Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. |
|-------------------------------|---|

|                        |                         |
|------------------------|-------------------------|
| <b>Hand protection</b> | Wear protective gloves. |
|------------------------|-------------------------|

**9. Physical & Chemical Properties****Appearance**

|                       |         |
|-----------------------|---------|
| <b>Physical state</b> | Liquid. |
|-----------------------|---------|

|             |         |
|-------------|---------|
| <b>Form</b> | Liquid. |
|-------------|---------|

|              |        |
|--------------|--------|
| <b>Color</b> | Black. |
|--------------|--------|

|             |                         |
|-------------|-------------------------|
| <b>Odor</b> | Mild. Hydrocarbon-like. |
|-------------|-------------------------|

|                       |                |
|-----------------------|----------------|
| <b>Odor threshold</b> | Not available. |
|-----------------------|----------------|

|           |                |
|-----------|----------------|
| <b>pH</b> | Not available. |
|-----------|----------------|

|                       |                   |
|-----------------------|-------------------|
| <b>Vapor pressure</b> | 3 mm Hg estimated |
|-----------------------|-------------------|

|                      |     |
|----------------------|-----|
| <b>Vapor density</b> | 4.9 |
|----------------------|-----|

|                      |                           |
|----------------------|---------------------------|
| <b>Boiling point</b> | 347 °F (175 °C) estimated |
|----------------------|---------------------------|

|                                     |                |
|-------------------------------------|----------------|
| <b>Melting point/Freezing point</b> | Not available. |
|-------------------------------------|----------------|

|                           |                |
|---------------------------|----------------|
| <b>Solubility (water)</b> | Not available. |
|---------------------------|----------------|

|                         |                |
|-------------------------|----------------|
| <b>Specific gravity</b> | Not available. |
|-------------------------|----------------|

|                         |                |
|-------------------------|----------------|
| <b>Relative density</b> | Not available. |
|-------------------------|----------------|

|                    |                    |
|--------------------|--------------------|
| <b>Flash point</b> | 101.0 °F (38.3 °C) |
|--------------------|--------------------|

|   |               |
|---|---------------|
| <b>Flammability limits in air, upper, % by volume</b> | 5 % estimated |
|---|---------------|

|   |                 |
|---|-----------------|
| <b>Flammability limits in air, lower, % by volume</b> | 0.7 % estimated |
|---|-----------------|

|                                  |                           |
|----------------------------------|---------------------------|
| <b>Auto-ignition temperature</b> | 410 °F (210 °C) estimated |
|----------------------------------|---------------------------|

|            |                |
|------------|----------------|
| <b>VOC</b> | 0.8 - 0.98 g/l |
|------------|----------------|

|                         |                |
|-------------------------|----------------|
| <b>Evaporation rate</b> | Not available. |
|-------------------------|----------------|

|                  |                |
|------------------|----------------|
| <b>Viscosity</b> | 3500 - 6500 cP |
|------------------|----------------|

|  |                |
|--|----------------|
| <b>Partition coefficient (n-octanol/water)</b> | Not available. |
|--|----------------|

**Other data**

|                |                        |
|----------------|------------------------|
| <b>Density</b> | 0.90 g/cm <sup>3</sup> |
|----------------|------------------------|

|                                    |                 |
|------------------------------------|-----------------|
| <b>Explosive limit - lower (%)</b> | 0.7 % estimated |
|------------------------------------|-----------------|

|                                    |               |
|------------------------------------|---------------|
| <b>Explosive limit - upper (%)</b> | 5 % estimated |
|------------------------------------|---------------|

Flammability (solid, gas) Not applicable.

## 10. Chemical Stability & Reactivity Information

|   |   |
|---|---|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.   |
| <b>Conditions to avoid</b>                | Avoid temperatures exceeding the flash point. Contact with incompatible materials.            |
| <b>Incompatible materials</b>             | Strong oxidizing agents.  |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.  |
| <b>Possibility of hazardous reactions</b> | Hazardous polymerization does not occur.  |

## 11. Toxicological Information

### Toxicological data

| Components   | Species  | Test Results   |
|--|--|--|
| Carbon Black (CAS 1333-86-4)                                   |  |  |
| <b>Acute</b>   |  |  |
| <b>Oral</b>  |  |  |
| LD50   | Rat  | > 8000 mg/kg   |
| <b>Toxicological information</b>                               | Occupational exposure to the substance or mixture may cause adverse effects.                                     |  |
| <b>Acute effects</b>   |  |  |
| <b>Sensitization</b>   | Not classified.  |  |
| <b>Chronic effects</b>   | Hazardous by WHMIS criteria. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.  |  |
| <b>Carcinogenicity</b>   | Hazardous by WHMIS criteria. Cancer hazard.  |  |
| <b>ACGIH Carcinogens</b>                                       |  |  |
| Carbon Black (CAS 1333-86-4)                                   |  | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) |  | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| <b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>  |  |  |
| Carbon Black (CAS 1333-86-4)                                   |  | 2B Possibly carcinogenic to humans.                              |
| Stoddard Solvent (CAS 8052-41-3)                               |  | 3 Not classifiable as to carcinogenicity to humans.              |
| <b>Skin corrosion/irritation</b>                               | Prolonged skin contact may cause temporary irritation.   |  |
| <b>Serious eye damage/irritation</b>                           | Direct contact with eyes may cause temporary irritation.   |  |
| <b>Mutagenicity</b>  | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |  |
| <b>Reproductive effects</b>                                    | Mutagenic effects. May cause reproductive system disorder and/or damage.   |  |
| <b>Teratogenicity</b>  | Not available.   |  |
| <b>Symptoms and target organs</b>                              | Direct contact with eyes may cause temporary irritation.   |  |
| <b>Synergistic materials</b>                                   | Not available.   |  |
| <b>Further information</b>                                     | Symptoms may be delayed.   |  |

## 12. Ecological Information

### Ecotoxicological data

| Product  | Species   | Test Results                    |
|--|---|---------------------------------|
| CIM 1000 Premix  |   |                                 |
| <b>Aquatic</b>   |   |                                 |
| Fish   | LC50 Fish   | 40.576 mg/l, 96 hours estimated |
| Components   | Species   | Test Results                    |
| Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8) |   |                                 |
| Fish   | LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss) | 2.9 mg/l, 96 hours              |

|  |  |
|--|--|
| <b>Ecotoxicity</b>                               | Contains a substance which causes risk of hazardous effects to the environment.  |
| <b>Environmental effects</b>                     | An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  |
| <b>Aquatic toxicity</b>                          | The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. |
| <b>Persistence and degradability</b>             | No data is available on the degradability of this product.   |
| <b>Bioaccumulation / accumulation</b>            |  |
| <b>Partition coefficient</b><br>Stoddard Solvent | 3.16 - 7.15  |
| <b>Mobility in environmental media</b>           | No data available for this product.  |
| <b>Other adverse effects</b>                     | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.            |

### 13. Disposal Considerations

|  |  |
|--|--|
| <b>Disposal instructions</b>                 | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.      |
| <b>Waste from residues / unused products</b> | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| <b>Contaminated packaging</b>                | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.       |

### 14. Transport Information

#### TDG

Not regulated as dangerous goods.

This material can be reclassified as non-hazardous for ground transportation per TDG 1.33. This material can also be shipped as UN1139 Coating Solutions, Class 3, PGIII.

#### IATA

|                                     |  |
|-------------------------------------|--|
| <b>UN number</b>                    | UN1139   |
| <b>UN proper shipping name</b>      | Coating solution (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining) (Asphalt, Stoddard solvent) |
| <b>Transport hazard class(es)</b>   |  |
| <b>Class</b>                        | 3  |
| <b>Subsidiary risk</b>              | -  |
| <b>Packing group</b>                | III  |
| <b>Environmental hazards</b>        | No.  |
| <b>ERG Code</b>                     | 3L   |
| <b>Special precautions for user</b> | Read safety instructions, MSDS and emergency procedures before handling.   |
| <b>Other information</b>            |  |
| <b>Passenger and cargo aircraft</b> | Allowed with restrictions.   |
| <b>Cargo aircraft only</b>          | Allowed with restrictions.   |

#### IMDG

|   |  |
|---|--|
| <b>UN number</b>  | UN1139   |
| <b>UN proper shipping name</b>  | COATING SOLUTION (includes surface treatments or coatings used for industrial purposes such as vehicle under-coating, drum or barrel lining) (Asphalt, Stoddard solvent) |
| <b>Transport hazard class(es)</b>   |  |
| <b>Class</b>  | 3  |
| <b>Subsidiary risk</b>  | -  |
| <b>Packing group</b>  | III  |
| <b>Environmental hazards</b>  |  |
| <b>Marine pollutant</b>   | No.  |
| <b>EmS</b>  | F-E, S-E   |
| <b>Special precautions for user</b>   | Read safety instructions, MSDS and emergency procedures before handling.   |
| <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b> | Not established.   |



## 15. Regulatory Information

### Canadian regulations

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

### WHMIS status

Controlled

### WHMIS classification

B3 - Combustible Liquids  
D2A - Other Toxic Effects-VERY TOXIC  
D2B - Other Toxic Effects-TOXIC

### WHMIS labeling



### International Inventories

| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia                   | Australian Inventory of Chemical Substances (AICS)                     | Yes                    |
| Canada                      | Domestic Substances List (DSL)   | Yes                    |
| Canada                      | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                       | Inventory of Existing Chemical Substances in China (IECSC)             | Yes                    |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)  | Yes                    |
| New Zealand                 | New Zealand Inventory  | Yes                    |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | Yes                    |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other Information

### Recommended use

Use in accordance with supplier's recommendations.

### HMIS® ratings

Health: 2\*  
Flammability: 3  
Physical hazard: 0

### NFPA ratings

Health: 2  
Flammability: 3  
Instability: 0

### Disclaimer

The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.

### Prepared by

Dan Libby

### Revision information

This document has undergone significant changes and should be reviewed in its entirety.