

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	CIM 1000 Premix
Registration number	-
Synonyms	None.
Issue date	13-July-2016
Version number	01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Waterproofing, chemical containment, secondary containment
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	CIM INDUSTRIES INC	
Address	6900 NELMS STREET HOUSTON, TX 77061 United States	
Division	A CHASE CORPORATION COMPANY	
Telephone	General Assistance	800 543-3458
e-mail	info@chasecorp.com	
Contact person	Not available.	

1.4. Emergency telephone number	Chemtrec (US - 24 hrs)	800 424-9300
	Chemtrec (INTL - 24 hrs)	703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification F;R11, Carc. Cat. 2;R45, Muta. Cat. 2;R46

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 3	H226 - Flammable liquid and vapour.
-------------------	------------	-------------------------------------

Health hazards

Germ cell mutagenicity	Category 1B	H340 - May cause genetic defects.
Carcinogenicity	Category 1B	H350 - May cause cancer.
Specific target organ toxicity - repeated exposure	Category 2	H373 - May cause damage to organs through prolonged or repeated exposure.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
--	------------	---

Hazard summary

Physical hazards	Highly flammable.
Health hazards	May cause cancer. May cause heritable genetic damage. Occupational exposure to the substance or mixture may cause adverse health effects.
Environmental hazards	Not classified for hazards to the environment.
Specific hazards	None known.
Main symptoms	Direct contact with eyes may cause temporary irritation. Prolonged exposure may cause chronic effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Stoddard solvent

Hazard pictograms



Signal word Danger

Hazard statements

H226	Flammable liquid and vapour.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P242	Use non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist or vapour.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P308 + P313	IF exposed or concerned: Get medical advice/attention.
P370 + P378	In case of fire: Use appropriate media to extinguish.

Storage

P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Supplemental label information 91,65 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Distillates (petroleum), hydrotreated light	5 - < 10	64742-47-8 265-149-8	-	649-422-00-2	

Classification: **DSD:** Xn;R65
CLP: Asp. Tox. 1;H304, Aquatic Chronic 2;H411

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Stoddard solvent	1 - < 3	8052-41-3 232-489-3	-	649-345-00-4	
Classification:	DSD:	Carc. Cat. 2;R45, Muta. Cat. 2;R46, Xn;R65-48/20			P
	CLP:	Flam. Liq. 3;H226, Asp. Tox. 1;H304, Muta. 1B;H340, Carc. 1B;H350, STOT RE 1;H372			P

Other components below reportable levels 80 - < 90

List of abbreviations and symbols that may be used above

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed Direct contact with eyes may cause temporary irritation. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.

For emergency responders	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.
6.4. Reference to other sections	For personal protection, see section 8. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not breathe mist or vapour. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m ³	Fume.
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m ³	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	200 mg/m ³	Vapor.
Stoddard solvent (CAS 8052-41-3)	TWA	533 mg/m ³	
		100 ppm	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Asphalt (CAS 8052-42-4)	STEL	10 mg/m ³
	TWA	5 mg/m ³
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	300 mg/m ³

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Asphalt (CAS 8052-42-4)	MAC	5 mg/m ³
	STEL	10 mg/m ³
Carbon black (CAS 1333-86-4)	MAC	3,5 mg/m ³
	STEL	7 mg/m ³

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m ³	Fume.
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m ³	

Czech Republic. OELs. Government Decree 361

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	2 mg/m ³	Dust.

Denmark. Exposure Limit Values

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TLV	1 mg/m ³	Dust.
Carbon black (CAS 1333-86-4)	TLV	3,5 mg/m ³	
Stoddard solvent (CAS 8052-41-3)	TLV	145 mg/m ³	
		25 ppm	

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m ³	Vapor.
Stoddard solvent (CAS 8052-41-3)	STEL	600 mg/m ³	
	TWA	100 ppm	
		300 mg/m ³	
		50 ppm	

Finland. Workplace Exposure Limits

Components	Type	Value
Carbon black (CAS 1333-86-4)	STEL	7 mg/m ³
	TWA	3,5 mg/m ³
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	500 mg/m ³

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Carbon black (CAS 1333-86-4)	VME	3,5 mg/m ³

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	140 mg/m ³	Vapor and aerosol.
		20 ppm	Vapor and aerosol.

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Asphalt (CAS 8052-42-4)	TWA	5 mg/m ³
Carbon black (CAS 1333-86-4)	STEL	7 mg/m ³
	TWA	3,5 mg/m ³
Stoddard solvent (CAS 8052-41-3)	STEL	720 mg/m ³
	TWA	125 ppm
		575 mg/m ³
		100 ppm

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m ³	Fume.
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m ³	

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value	Form
Stoddard solvent (CAS 8052-41-3)	TWA	145 mg/m3	
		25 ppm	

Ireland. Occupational Exposure Limits

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	STEL	10 mg/m3	Fume.
	TWA	0,5 mg/m3	Fume.
Carbon black (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3,5 mg/m3	
Stoddard solvent (CAS 8052-41-3)	TWA	573 mg/m3	
		100 ppm	

Italy. Occupational Exposure Limits

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	0,5 mg/m3	Inhalable fraction.
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	STEL	500 mg/m3	
	TWA	350 mg/m3	

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TLV	5 mg/m3	Fume.
Carbon black (CAS 1333-86-4)	TLV	3,5 mg/m3	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TLV	275 mg/m3	
		40 ppm	

Poland. MACs. Regulation regarding maximum permissible concentrations and intensities of harmful factors in the work environment, Annex 1

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	STEL	10 mg/m3	Inhalable fraction.
	TWA	5 mg/m3	Inhalable fraction.
Carbon black (CAS 1333-86-4)	TWA	4 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	STEL	300 mg/m3	
	TWA	100 mg/m3	
Stoddard solvent (CAS 8052-41-3)	STEL	900 mg/m3	
	TWA	300 mg/m3	

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	0,5 mg/m3	Inhalable fume.
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m3	Fume.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	Fume.

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value	Form
Stoddard solvent (CAS 8052-41-3)	STEL	1000 mg/m3	
	TWA	700 mg/m3	

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	2 mg/m3	
Stoddard solvent (CAS 8052-41-3)	STEL	600 mg/m3	
		100 ppm	
	TWA	300 mg/m3 50 ppm	

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	10 ppm	Vapor and aerosol.

Spain. Occupational Exposure Limits

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	0,5 mg/m3	Aerosol
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m3	

Sweden. Occupational Exposure Limit Values

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	STEL	500 mg/m3	
	TWA	350 mg/m3	
Stoddard solvent (CAS 8052-41-3)	STEL	300 mg/m3	
		50 ppm	
	TWA	150 mg/m3 25 ppm	

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	10 mg/m3	Vapor and aerosol.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Fume.
	STEL	7 mg/m3	
Carbon black (CAS 1333-86-4)		3,5 mg/m3	
	TWA		

Biological limit values No biological exposure limits noted for the ingredient(s).**Recommended monitoring procedures** Follow standard monitoring procedures.**Derived no-effect level (DNEL)** Not available.**Predicted no effect concentrations (PNECs)** Not available.**8.2. Exposure controls****Appropriate engineering controls** Good general ventilation should be used (see CIM IG-9 for additional details). Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.**Individual protection measures, such as personal protective equipment****General information** Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
- Other	Wear suitable protective clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Colour	Black.
Odour	Mild. Hydrocarbon-like.
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	175 °C (347 °F) estimated
Flash point	38,3 °C (101,0 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	0,7 % estimated
Flammability limit - upper (%)	5 % estimated
Explosive limit - lower (%)	0,7 % estimated
Explosive limit – upper (%)	5 % estimated
Vapour pressure	3 mm Hg estimated
Vapour density	4,9
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Solubility (other)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	210 °C (410 °F) estimated
Decomposition temperature	Not available.
Viscosity	3500 - 6500 cP
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2. Other information

Density	0,90 g/cm ³
VOC (Weight %)	0,8 - 0,98 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
-------------------------	---

10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms Exposure may cause temporary irritation, redness, or discomfort.

11.1. Information on toxicological effects

Acute toxicity	No data available.
Skin corrosion/irritation	Due to partial or complete lack of data the classification is not possible.
Serious eye damage/eye irritation	Due to partial or complete lack of data the classification is not possible.
Respiratory sensitisation	Due to partial or complete lack of data the classification is not possible.
Skin sensitisation	Due to partial or complete lack of data the classification is not possible.
Germ cell mutagenicity	May cause genetic defects.
Carcinogenicity	May cause cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Stoddard solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.
Mixture versus substance information	No information available.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.

Components	Species	Test results
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Aquatic		
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)
		2,9 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)
Stoddard solvent 3,16 - 7,15

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment	Not available.
12.6. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1139
14.2. UN proper shipping name	COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining) (vapour pressure at 50 °C more than 110 kPa) (Asphalt, Stoddard solvent)
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	33
Tunnel restriction code	D/E
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1139
14.2. UN proper shipping name	COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining) (vapour pressure at 50 °C not more than 110 kPa) (Asphalt, Stoddard solvent)
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1139
14.2. UN proper shipping name	Coating Solution ([includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining) (vapour pressure at 50 °c not more than 110 kpa)] (Asphalt, Stoddard solvent)
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1139
------------------------	--------

14.2. UN proper shipping name	Coating solution (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining) (Asphalt, Stoddard solvent)
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	II
14.5. Environmental hazards	No.
ERG Code	3L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1139
14.2. UN proper shipping name	COATING SOLUTION (includes surface treatments or coatings used for industrial purposes such as vehicle under-coating, drum or barrel lining) (Asphalt, Stoddard solvent)
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	II
14.5. Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Not established.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Stoddard solvent (CAS 8052-41-3)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Stoddard solvent (CAS 8052-41-3)

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

Stoddard solvent (CAS 8052-41-3)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances

Not listed.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Stoddard solvent (CAS 8052-41-3)

Directive 94/33/EC on the protection of young people at work, as amended

Stoddard solvent (CAS 8052-41-3)

Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. Pregnant women should not work with the product, if there is the least risk of exposure. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R11 Highly flammable.
R45 May cause cancer.
R46 May cause heritable genetic damage.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R65 Harmful: may cause lung damage if swallowed.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H340 May cause genetic defects.
H350 May cause cancer.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Revision information

Product and Company Identification: Product and Company Identification
Transport Information: Material Transportation Information
GHS: Classification

Training information

Follow training instructions when handling this material.

Issued by

Dan Libby

Disclaimer

The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.