



SAFETY DATA SHEET

1. Identification

Name of the substance or mixture (trade name)	CIM 1000 Premix	
Major recommended uses for the substance or mixture	Waterproofing, chemical containment, secondary containment	
Specific restrictions for use of the substance or mixture	Not available.	
Manufacturer/Importer/Distributor information		
Manufacturer		
Company name	CIM INDUSTRIES INC	
Address	6900 NELMS STREET HOUSTON, TX 77061 United States	
Division	A CHASE CORPORATION COMPANY	
Telephone	General Assistance	800 543-3458
Website		
E-mail	info@chasecorp.com	
Emergency telephone number	Chemtrec (US - 24 hrs)	800 424-9300
	Chemtrec (INTL - 24 hrs)	703-527-3887

2. Hazards identification

Classification of the substance or mixture

Physical hazards	Flammable liquids	Category 3
Health hazards	Acute toxicity, inhalation	Category 3
	Skin corrosion/irritation	Category 3
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3

GHS labeling elements, including precautionary statements

Hazard symbol(s)



Signal word

Danger

Hazard statement(s)

Flammable liquid and vapor. Causes mild skin irritation. Toxic if inhaled. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor. If skin irritation occurs: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards which do not result in classification	None known.
Supplemental information	88.83% of the mixture consists of component(s) of unknown acute inhalation toxicity. 91.65% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 91.65% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixture

Common chemical name or technical name	CAS number	Concentration or concentration range
Distillates (petroleum), Hydrotreated Light	64742-47-8	5 - < 10
Stoddard solvent	8052-41-3	1 - < 3
Carbon black	1333-86-4	1 - < 3
Other components below reportable levels		80 - < 90

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Mild skin irritation. Prolonged exposure may cause chronic effects.
Personal protection for first-aid responders	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
Notes to physician	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Means of fire extinguishing

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special fire fighting procedures	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Protective measures taken by firefighting crews	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Control measures for spills and leaks

Personal precautions, protective equipment and emergency procedures

To be taken by those who are not involved in rendering emergency services Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

To be taken by those who are involved in rendering emergency services Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Control parameters Follow standard monitoring procedures.

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	

Argentina. OELs. Law 19587 (Establishing the Conditions for Health and Safety in the Workplace) and Decree 351/79 Article 61, Annex III, as amended

Components	Type	Value
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m ³
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm

Chile. OELs. Decree No. 594, arts. 61 & 66: Regulating Basic Health and Environmental Conditions in the Workplace and Setting Permissible Levels of Exposure to Chemical and Physical Agents

Components	Type	Value
Carbon black (CAS 1333-86-4)	TWA	2.8 mg/m ³

Ecuador. OELs (INEN 2266:2013, 2013-01 2nd rev.: Transport, storage and handling of hazardous materials. Requirements. 1st ed., 1/29, 2013)

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m ³	Inhalable fraction.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	

Paraguay. Decree No. 14.390/92 that approves the General Technical Regulation of Safety, Hygiene and Medicine in the Workplace

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m ³	Inhalable fraction.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	

Peru. OELs. Decreto Supremo 015-2005-SA (Reglamento sobre Valores Limites Permisibles para Agentes Químicos en el Ambiente de Trabajo)

Components	Type	Value
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m ³

Venezuela. OELs. (COVENIN 2253: Permissible Environmental Concentration Limits for Chemical Substances in Workplaces and Biological Exposure Indices)

Components	Type	Value
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m ³
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Good general ventilation should be used (see CIM IG-9 for additional details). Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Personal protective measures	
Eyes and face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear suitable protective clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Black.
Odor	Mild. Hydrocarbon-like.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling temperature range	347 °F (175 °C) estimated
Flash point	101.0 °F (38.3 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.7 % estimated
Flammability limit - upper (%)	5 % estimated
Explosive limit - lower (%)	0.7 % estimated
Explosive limit - upper (%)	5 % estimated
Vapor pressure	3 mm Hg estimated
Vapor density	4.9
Relative density	Not available.
Solubility(ies)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
Viscosity	3500 - 6500 cP
Other physical and chemical parameters	
Density	0.90 g/cm ³
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC (Weight %)	0.8 - 0.98 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Toxic if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Causes mild skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms	Mild skin irritation.
Acute toxicity	Toxic if inhaled.

Components	Species	Test Results
------------	---------	--------------

Carbon black (CAS 1333-86-4)

Acute

Oral

LD50

Rat

> 8000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin irritation and corrosion

Causes mild skin irritation.

Serious eye damage/eye irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

ACGIH Carcinogens

Carbon black (CAS 1333-86-4)

A3 Confirmed animal carcinogen with unknown relevance to humans.

Argentina. OELs. Law 19587 (Establishing the Conditions for Health and Safety in the Workplace) and Decree 351/79 Article 61, Annex III, as amended

Carbon black (CAS 1333-86-4)

A4 Not classifiable as a human carcinogen.

Colombia. OELs. Resolution No. 02400: Norms Concerning Working Conditions, Health and Safety in the Workplace

Carbon black (CAS 1333-86-4)

A3 Animal carcinogen.

Ecuador. OELs (INEN 2266:2013, 2013-01 2nd rev.: Transport, storage and handling of hazardous materials. Requirements. 1st ed., 1/29, 2013)

Carbon black (CAS 1333-86-4)

Group A3 Confirmed animal carcinogen with unknown relevance to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4)

2B Possibly carcinogenic to humans.

Stoddard solvent (CAS 8052-41-3)

3 Not classifiable as to carcinogenicity to humans.

Paraguay. Decree No. 14.390/92 that approves the General Technical Regulation of Safety, Hygiene and Medicine in the Workplace

Carbon black (CAS 1333-86-4)

A3 Confirmed animal carcinogen with unknown relevance to humans.

Venezuela. OELs. (COVENIN 2253: Permissible Environmental Concentration Limits for Chemical Substances in Workplaces and Biological Exposure Indices)

Carbon black (CAS 1333-86-4)

A4 Not classifiable as a human carcinogen.

Toxic to reproduction

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
------------	---------	--------------

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Fish

LC50

Rainbow trout, donaldson trout
(Oncorhynchus mykiss)

2.9 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)	
Stoddard solvent	3.16 - 7.15
Bioconcentration factor (BCF)	Not available.

Mobility in soil No data available for this product.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Considerations on final disposal

Recommended methods for final destination

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
Local disposal regulations	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. Transport information

National regulations

ANTT

UN number	UN1139
UN proper shipping name	COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining) (Distillates (petroleum), Hydrotreated Light, Stoddard solvent)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

International regulations

IATA

UN number	UN1139
UN proper shipping name	Coating solution (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining) (Asphalt, Stoddard solvent)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1139
UN proper shipping name	COATING SOLUTION (includes surface treatments or coatings used for industrial purposes such as vehicle under-coating, drum or barrel lining) (Asphalt, Stoddard solvent)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

ANTT; IATA; IMDG



15. Regulatory information

Federal regulations This chemical product safety data sheet was prepared in accordance with the Brazilian Standard (ABNT NBR 14725-4: (Safety data sheet for chemicals (SDS))).

Chile. Decree No. 594, art. 20: List of Hazardous Wastes that must be Registered with the Sanitary Authority

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Ecuador. Hazardous, Restricted & Prohibited Chemicals: Table 1 listed substance

Stoddard solvent (CAS 8052-41-3)

Peru. Controlled Drugs and Precursors, Chemical Inputs and Products Control

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Venezuela. Chemical Precursors (Official Gazette No. 34.741, List I & II)

Not regulated.

International regulations

Montreal Protocol

Not applicable.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Basel Convention

Not applicable.

16. Other information

Significant information, yet not specifically related to the previous sections Not available.

Legends and abbreviations Not available.

Revision information Product and Company Identification: Product and Company Identification
Transport Information: Material Transportation Information
GHS: Classification

Disclaimer The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.