

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	CIM 1061 Premix
Registration number	-
Synonyms	None.
Issue date	05-19-2015
Version number	01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Waterproofing, chemical containment, secondary containment
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	CIM INDUSTRIES INC
Address	A CHASE CORPORATION COMPANY 6900 NELMS STREET US

Division

Telephone	General Assistance	800 543-3458
e-mail	info@chasecorp.com	
Contact person	Not available.	

1.4. Emergency telephone number	Chemtrec (US - 24 hrs)	800 424-9300
	Chemtrec (INTL - 24 hrs)	703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification R10, Carc. Cat. 2;R45, Muta. Cat. 2;R46, Xn;R20, R52/53

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 3	H226 - Flammable liquid and vapor.
-------------------	------------	------------------------------------

Health hazards

Germ cell mutagenicity	Category 1B	H340 - May cause genetic defects.
Carcinogenicity	Category 1B	H350 - May cause cancer.
Specific target organ toxicity - repeated exposure	Category 2	H373 - May cause damage to organs through prolonged or repeated exposure.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
--	------------	---

Hazard summary

Physical hazards	Flammable.
Health hazards	May cause cancer. May cause heritable genetic damage. Also harmful by inhalation. Occupational exposure to the substance or mixture may cause adverse health effects.
Environmental hazards	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Specific hazards	None known.
Main symptoms	Irritation of eyes and mucous membranes. Prolonged exposure may cause chronic effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Stoddard solvent

Hazard pictograms



Signal word Danger

Hazard statements

H226	Flammable liquid and vapor.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist or vapor.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P370 + P378	In case of fire: Use appropriate media to extinguish.

Storage

P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Supplemental label information 89,12% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), Hydrotreated Light	5 - < 10	64742-47-8 265-149-8	-	649-422-00-2	
Classification:	DSD: Xn;R65				
	CLP: Asp. Tox. 1;H304, Aquatic Chronic 2;H411				

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Stoddard solvent	1 - < 3	8052-41-3 232-489-3	-	649-345-00-4	
Classification:	DSD:	Carc. Cat. 2;R45, Muta. Cat. 2;R46, Xn;R65-48/20			P
	CLP:	Flam. Liq. 3;H226, Asp. Tox. 1;H304, Muta. 1B;H340, Carc. 1B;H350, STOT RE 1;H372			P
Carbon black	1 - < 3	1333-86-4 215-609-9	-	-	
Classification:	DSD:	-			
	CLP:	Carc. 2;H351			

Other components below reportable levels 80 - < 90

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed Irritation of eyes and mucous membranes. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Flammable liquid and vapor.

5.1. Extinguishing media

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains.

7.2. Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Refrigeration recommended. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m ³	Fume.
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m ³	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	200 mg/m ³	Vapor.
Stoddard solvent (CAS 8052-41-3)	TWA	533 mg/m ³	
		100 ppm	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Asphalt (CAS 8052-42-4)	STEL	10 mg/m ³
	TWA	5 mg/m ³
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	300 mg/m ³

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Asphalt (CAS 8052-42-4)	MAC	5 mg/m3
	STEL	10 mg/m3
Carbon black (CAS 1333-86-4)	MAC	3,5 mg/m3
	STEL	7 mg/m3

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	Fume.
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m3	

Czech Republic. OELs. Government Decree 361

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	2 mg/m3	Dust.

Denmark. Exposure Limit Values

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TLV	1 mg/m3	Dust.
Carbon black (CAS 1333-86-4)	TLV	3,5 mg/m3	
Stoddard solvent (CAS 8052-41-3)	TLV	145 mg/m3	
		25 ppm	

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	Vapor.
Stoddard solvent (CAS 8052-41-3)	STEL	600 mg/m3	
		100 ppm	
		300 mg/m3	
	TWA	50 ppm	

Finland. Workplace Exposure Limits

Components	Type	Value
Carbon black (CAS 1333-86-4)	STEL	7 mg/m3
	TWA	3,5 mg/m3
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	500 mg/m3

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Carbon black (CAS 1333-86-4)	VME	3,5 mg/m3

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	140 mg/m3	Vapor and aerosol.
		20 ppm	Vapor and aerosol.

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3
Carbon black (CAS 1333-86-4)	STEL	7 mg/m3
	TWA	3,5 mg/m3
Stoddard solvent (CAS 8052-41-3)	STEL	720 mg/m3
		125 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
	TWA	575 mg/m3 100 ppm

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	Fume.
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m3	
Stoddard solvent (CAS 8052-41-3)	TWA	145 mg/m3 25 ppm	

Ireland. Occupational Exposure Limits

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	STEL	10 mg/m3	Fume.
	TWA	0,5 mg/m3	Fume.
Carbon black (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3,5 mg/m3	
Stoddard solvent (CAS 8052-41-3)	TWA	573 mg/m3 100 ppm	

Italy. Occupational Exposure Limits

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	0,5 mg/m3	Inhalable fraction.
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	STEL	500 mg/m3
	TWA	350 mg/m3

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TLV	5 mg/m3	Fume.
Carbon black (CAS 1333-86-4)	TLV	3,5 mg/m3	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TLV	275 mg/m3 40 ppm	

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Fume.
Carbon black (CAS 1333-86-4)	TWA	4 mg/m3	Total dust.
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	STEL	300 mg/m3	
	TWA	100 mg/m3	
Stoddard solvent (CAS 8052-41-3)	STEL	900 mg/m3	
	TWA	300 mg/m3	

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	0,5 mg/m3	Inhalable fume.

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m3	Fume.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	Fume.
Stoddard solvent (CAS 8052-41-3)	STEL	1000 mg/m3	
	TWA	700 mg/m3	

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	2 mg/m3	
Stoddard solvent (CAS 8052-41-3)	STEL	600 mg/m3	
	TWA	100 ppm 300 mg/m3 50 ppm	

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	10 ppm	Vapor and aerosol.

Spain. Occupational Exposure Limits

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	0,5 mg/m3	Aerosol.
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m3	

Sweden. Occupational Exposure Limit Values

Components	Type	Value	Form
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	STEL	500 mg/m3	
Stoddard solvent (CAS 8052-41-3)	TWA	350 mg/m3	
	STEL	300 mg/m3	
	TWA	50 ppm 150 mg/m3 25 ppm	

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	10 mg/m3	Vapor and aerosol.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Fume.
Carbon black (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3,5 mg/m3	

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no-effect level (DNEL) Not available.

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Chemical respirator with organic vapor cartridge and full facepiece.
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves.
- Other	Wear suitable protective clothing. Use of an impervious apron is recommended.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Contain spills and prevent releases and observe national regulations on emissions. Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Black.
Odor	Mild. Hydrocarbon-like.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	347 °F (175 °C) estimated
Flash point	101,0 °F (38,3 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0,7 % estimated
Flammability limit - upper (%)	5 % estimated
Explosive limit - lower (%)	0,7 % estimated
Explosive limit - upper (%)	5 % estimated
Vapor pressure	3 mm Hg estimated
Vapor density	4,9
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Solubility (other)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
Viscosity	3500 - 6500 cP
Explosive properties	Not available.
Oxidizing properties	Not available.

9.2. Other information

Density	0,90 g/cm ³
VOC (Weight %)	0,8 - 0,98 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidizing agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Inhalation	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms Irritation of eyes and mucous membranes.

11.1. Information on toxicological effects

Components	Species	Test Results
Carbon black (CAS 1333-86-4)		
Acute		
<i>Oral</i>		
LD50	Rat	> 8000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Due to partial or complete lack of data the classification is not possible.
Serious eye damage/eye irritation	Due to partial or complete lack of data the classification is not possible.
Respiratory sensitization	Due to partial or complete lack of data the classification is not possible.
Skin sensitization	Due to partial or complete lack of data the classification is not possible.
Germ cell mutagenicity	May cause genetic defects.
Carcinogenicity	May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Stoddard solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.
Mixture versus substance information	No information available.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Components	Species	Test Results
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		2,9 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability	No data is available on the degradability of this product.
12.3. Bioaccumulative potential	Not available.
Partition coefficient n-octanol/water (log Kow)	
Stoddard solvent	3,16 - 7,15
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1139
14.2. UN proper shipping name	COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	30
Tunnel restriction code	D/E
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1139
14.2. UN proper shipping name	COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1139
14.2. UN proper shipping name	Coating Solution ([includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining) (having a flash -point below 23 °c and viscous according to 2.2.3.1.4)]
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1139
14.2. UN proper shipping name	Coating solution (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining)
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	No.
ERG Code	3L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

14.1. UN number	UN1139
14.2. UN proper shipping name	COATING SOLUTION (includes surface treatments or coatings used for industrial purposes such as vehicle under-coating, drum or barrel lining)
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E*
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	This substance/mixture is not intended to be transported in bulk.

ADN; ADR; IATA; IMDG; RID

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations**

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA

Not listed.

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Stoddard solvent (CAS 8052-41-3)

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Stoddard solvent (CAS 8052-41-3)

Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not listed.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Stoddard solvent (CAS 8052-41-3)

Directive 94/33/EC on the protection of young people at work

Stoddard solvent (CAS 8052-41-3)

Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Pregnant women should not work with the product, if there is the least risk of exposure.

National regulations

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work. Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable.

R20 Also harmful by inhalation.

R45 May cause cancer.

R46 May cause heritable genetic damage.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H340 May cause genetic defects.
H350 May cause cancer.
H351 Suspected of causing cancer by inhalation.
H351 Suspected of causing cancer by ingestion.
H351 Suspected of causing cancer by skin contact.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.