

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

CIM VOC COMPLIANT BONDING AGENT

of the mixture

Registration number

None. **Synonyms**

15-April-2016 Issue date

Version number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Bonding Agent for Urethane Coatings

Uses advised against None known. 1.3. Details of the supplier of the safety data sheet

Supplier

CIM INDUSTRIES INC Company name **Address** 6900 NELMS STREET

HOUSTON, TX 77061

Chemtrec (US - 24 hrs)

United States

Division A CHASE CORPORATION COMPANY

Telephone General Assistance 800 543-3458

e-mail info@chasecorp.com

Not available. **Contact person**

1.4. Emergency telephone

number

Chemtrec (INTL - 24 hrs) 703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

800 424-9300

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification F;R11, Xi;R36, R66-67 The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids H225 - Highly flammable liquid and Category 2

vapour.

Health hazards

exposure

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

dizziness.

Hazard summary

Physical hazards Highly flammable.

Material name: CIM VOC COMPLIANT BONDING AGENT

4 Version #: 01 Issue date: 15-April-2016

SDS BELGIUM

Health hazards Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause

drowsiness and dizziness. Occupational exposure to the substance or mixture may cause adverse

health effects.

Environmental hazards Not classified for hazards to the environment.

Specific hazards None known.

Main symptoms May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat.

Severe eye irritation. Irritation of eyes and mucous membranes. Symptoms may include stinging,

tearing, redness, swelling, and blurred vision.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 2-PROPANONE (ACETONE)

Hazard pictograms



Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapour.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.
P280 Wear eye protection/face protection.

P280 Wear protective gloves/eye protection/face protection.

Response

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P370 + P378 In case of fire: Use appropriate media to extinguish.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information % of the mixture consists of component(s) of unknown long-term hazards to the aquatic

environment. EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

% CAS-No. / EC **REACH Registration No.** INDEX No. **Chemical name Notes** No.

2-PROPANONE (ACETONE) 67-64-1 606-001-00-8 # 90 - 100

200-662-2

Classification: **DSD:** F:R11. Xi:R36. R66-67

CLP: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336

Other components below reportable levels < 1

List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008. DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance. PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the General information

material(s) involved, and take precautions to protect themselves. Wash contaminated clothing

before reuse.

4.1. Description of first aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON Inhalation

CENTRE or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth, Get medical attention if symptoms occur. Ingestion

4.2. Most important symptoms and effects, both acute and

delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing

media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising

from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. Specific methods

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapour. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Refrigeration recommended. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.

Components	Туре	Value	
2-PROPANONE (ACETONE) (CAS 67-64-1)	STEL	2420 mg/m3	
		1000 ppm	
	TWA	1210 mg/m3	
		500 ppm	
EU. Indicative Exposure Lir	nit Values in Directives 91/322/EEC,	2000/39/EC, 2006/15/EC, 2009/161/EU	
Components	Туре	Value	
2-PROPANONE (ACETONE) (CAS 67-64-1)	TWA	1210 mg/m3	
		500 ppm	
logical limit values	No biological exposure limits noted for the ingradient(s)		

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no-effect level (DNEL)

Not available. Not available.

Predicted no effect concentrations (PNECs)

8.2. Exposure controls

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

according to the CEN standards and in discussion with the supplier of the personal protective

equipment. Eye wash fountain and emergency showers are recommended.

Eye/face protection

Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

- Other Wear suitable protective clothing.

Respiratory protection Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Contain spills and prevent releases and observe national regulations on emissions. Environmental

manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Colour Colourless.
Odour Acetone.
Odour threshold Not available.
pH Not available.

Melting point/freezing point -94,7 °C (-138,46 °F) estimated Initial boiling point and boiling 56,05 °C (132,89 °F) estimated

range

Flash point -20,0 °C (-4,0 °F) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

2,6 %

(/0)

Flammability limit - upper 12,8 %

(%)

Vapour pressure30,6 kPa @25°CVapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) miscible
Solubility (other) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 465 °C (869 °F) estimated

Decomposition temperature Not available.

Viscosity 0,3 cP

Explosive propertiesNot available. **Oxidising properties**Not available.

9.2. Other information

Density 0,79 g/cm3 **Specific gravity** 0,79

VOC (Weight %) 0 g/l (Exempt solvent)

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stabilityMaterial is stable under normal conditions.

Acids

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

10.5. Incompatible materials

10.6. Hazardous

No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. May cause drowsiness and dizziness. Headache. Nausea,

vomiting.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Test results

5800 mg/kg

vision.

Species

11.1. Information on toxicological effects

Acute toxicity Narcotic effects.

2-PROPANONE (ACETON	IE) (CAS 67-64-1)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	20000 mg/kg
		20 ml/kg
Inhalation		
LC50	Rat	76 mg/l, 4 Hours
		50,1 mg/l, 8 Hours
Oral		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg

^{*} Estimates for product may be based on additional component data not shown.

Rat

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible.

Serious eye damage/eye

irritation

Components

Causes serious eye irritation.

Causes serious eye irritation.

Respiratory sensitisationDue to partial or complete lack of data the classification is not possible.Skin sensitisationDue to partial or complete lack of data the classification is not possible.Germ cell mutagenicityDue to partial or complete lack of data the classification is not possible.CarcinogenicityDue to partial or complete lack of data the classification is not possible.Reproductive toxicityDue to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

Other information Not available

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Components Species Test results

2-PROPANONE (ACETONE) (CAS 67-64-1)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 10294 - 17704 mg/l, 48 hours
Fish LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and

No data is available on the degradability of this product.

degradability

12.3. Bioaccumulative potential Not available.

Partition coefficient n-octanol/water (log Kow)

2-PROPANONE (ACETONE) -0,24

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT Not a PB

and vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1090

14.2. UN proper shipping ACETONE SOLUTION (2-PROPANONE (ACETONE))

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Hazard No. (ADR) 33
Tunnel restriction code D/E
14.4. Packing group II
14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN1090

14.2. UN proper shipping ACETONE, SOLUTION (2-PROPANONE (ACETONE))

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
14.4. Packing group ||
14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

UN1090 14.1. UN number

14.2. UN proper shipping Acetone solution (2-PROPANONE (ACETONE))

name

14.3. Transport hazard class(es)

3 Subsidiary risk 3 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1090

14.2. UN proper shipping Acetone solution (2-PROPANONE (ACETONE))

name

14.3. Transport hazard class(es)

3 Class Subsidiary risk 14.4. Packing group Ш 14.5. Environmental hazards No. **ERG Code**

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions.

Cargo aircraft only

IMDG

UN1090 14.1. UN number

ACETONE SOLUTION (2-PROPANONE (ACETONE)) 14.2. UN proper shipping

Not available.

name

14.3. Transport hazard class(es)

Class Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards Marine pollutant No.

F-E, S-D **EmS**

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of Marpol

and the IBC Code

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU** regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended 2-PROPANONE (ACETONE) (CAS 67-64-1)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances

2-PROPANONE (ACETONE) (CAS 67-64-1)

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended

2-PROPANONE (ACETONE) (CAS 67-64-1)

Directive 94/33/EC on the protection of young people at work, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws.

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations
15.2. Chemical safety

assessment

Follow national regulation for work with chemical agents. No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Full text of any statements or R-phrases and H-statements

under Sections 2 to 15 R11 Highly flammable.

R36 Irritating to eves.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Revision information Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties

Regulatory Information: VOC Regulations

Training information Follow training instructions when handling this material.

Issued by Dan Libby

Disclaimer

The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.