



We make a material difference

SAFETY DATA SHEET

1. Identification of the product

GHS product identifier **Tapecoat Wet Bond Epoxy Mastic Hardener**

Other means of identification Not available.

Recommended use of the chemical and restrictions on use

Recommended use Not available.

Recommended restrictions None known.

Suppliers details

Company name	Chase Corporation - Tapecoat Division	
Address	1527 Lyons Street Evanston, IL 60201 United States	
Telephone	General Assistance	800 543-3458
E-mail	info@chasecorp.com	
Emergency phone number	Chemtrec (US - 24 hrs)	800 424-9300
	Chemtrec (INTL - 24 hrs)	703-527-3887

2. Hazard identification

Classification of the substance or mixture

Physical hazards	Not classified.	
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, dermal	Category 4
	Skin corrosion/irritation	Category 1
	Serious eye damage/eye irritation	Category 1
	Sensitization, respiratory	Category 1
	Sensitization, skin	Category 1
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity - single exposure	Category 3 respiratory tract irritation
Environmental hazards	Hazardous to the aquatic environment — acute aquatic hazard	Category 2
	Hazardous to the aquatic environment — long-term aquatic hazard	Category 3

GHS label elements, including precautionary statements



Signal word Danger

Hazard statement Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of damaging fertility. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement**Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification

None known.

Supplemental information

60.49% of the mixture consists of component(s) of unknown acute oral toxicity. 60.49% of the mixture consists of component(s) of unknown acute dermal toxicity. 60.49% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 66.97% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients**Mixtures**

Chemical identity	Common name(s), synonym(s)	CAS number and other unique identifiers	Concentration
Bisphenol A		80-05-7	20 - < 30
2,2'-iminodi(ethylamine)		111-40-0	5 - < 10
BENZYL ALCOHOL		100-51-6	5 - < 10
Other components below reportable levels			60 - < 70

4. First-aid measures**Description of necessary first-aid measures****Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Take off immediately all contaminated clothing. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Difficulty in breathing. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures**Suitable extinguishing media**

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective actions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

Environmental precautions Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

Methods and materials for containment and cleaning up The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions to ensure safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Wash contaminated clothing before reuse. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Mexico. Occupational Exposure Limit Values

Components	Type	Value
2,2'-iminodi(ethylamine) (CAS 111-40-0)	TWA	4.2 mg/m3
		1 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2,2'-iminodi(ethylamine) (CAS 111-40-0)	TWA	1 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines**Mexico OELs: Skin designation**

2,2'-iminodi(ethylamine) (CAS 111-40-0)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

2,2'-iminodi(ethylamine) (CAS 111-40-0)

Can be absorbed through the skin.

Control banding approach

Not available.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance****Physical state**

Liquid.

Form

Liquid.

Color

Light amber.

Odor

Ammoniacal.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

-38.2 °F (-39 °C) estimated

Initial boiling point and boiling range

> 392 °F (> 200 °C)

Flash point

> 392.0 °F (> 200.0 °C)

Evaporation rate

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits**Flammability limit - lower (%)**

Not available.

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

Negligible

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)**Solubility (water)**

Insoluble

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

> 392 °F (> 200 °C)

Decomposition temperature

Not available.

Viscosity 3000 - 4000 cP

Other information

Density 1.12 g/cm³ estimated
Percent volatile 9 % estimated
Specific gravity 1 estimated
VOC (Weight %) 0 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability Material is stable under normal conditions.
Possibility of hazardous reactions Hazardous polymerization does not occur.
Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials Strong acids. Alkaline metals.
Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Causes digestive tract burns. Harmful if swallowed.
Inhalation Prolonged inhalation may be harmful. May cause irritation to the respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact Causes severe skin burns. Harmful in contact with skin. May cause an allergic skin reaction.
Eye contact Causes serious eye damage.
Symptoms Burning pain and severe corrosive skin damage. Difficulty in breathing. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity Harmful in contact with skin. Harmful if swallowed. May cause an allergic skin reaction. May cause respiratory irritation.

Product	Species	Test Results
Tapecoat Wet Bond Epoxy Mastic Hardener (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	22222.2227 mg/kg estimated
<i>Inhalation</i>		
LC100	Rat	2222.2222 mg/l, 8 Hours estimated
LC50	Rat	11111.1113 mg/l, 8 Hours estimated
<i>Oral</i>		
LD50	Mouse	6532.4458 mg/kg estimated
	Rabbit	21555.5547 mg/kg estimated
	Rat	4854.6304 mg/kg estimated
<i>Other</i>		
LD50	Guinea pig	1600 mg/kg estimated
	Mouse	840.0157 mg/kg estimated
	Rabbit	601.884 mg/kg estimated
	Rat	388.5323 mg/kg estimated
Components	Species	Test Results
2,2'-iminodi(ethylamine) (CAS 111-40-0)		
Acute		
<i>Oral</i>		
LD50	Rat	1080 mg/kg

Components	Species	Test Results
<i>Other</i>		
LD50	Guinea pig	162 mg/kg
	Mouse	71 mg/kg
	Rabbit	1090 mg/kg
	Rat	74 mg/kg
BENZYL ALCHOHOL (CAS 100-51-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	2000 mg/kg
<i>Inhalation</i>		
LC100	Rat	200 - 300 mg/l, 8 Hours
LC50	Rat	1000 mg/l, 8 Hours
<i>Oral</i>		
LD50	Mouse	1580 mg/kg
	Rabbit	1940 mg/kg
	Rat	1230 - 3100 mg/kg
<i>Other</i>		
LD50	Guinea pig	> 400 mg/kg
	Mouse	324 mg/kg
	Rat	53 mg/kg
Bisphenol A (CAS 80-05-7)		
Acute		
<i>Oral</i>		
LD50	Mouse	2500 mg/kg
	Rat	3300 mg/kg
<i>Other</i>		
LD50	Rabbit	150 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory or skin sensitization	
Respiratory sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive toxicity	Suspected of damaging fertility.
Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Other information	Not available.

12. Ecological information

Ecotoxicity	Toxic to aquatic life. Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.
--------------------	--

Product	Species		Test Results
Tapecoat Wet Bond Epoxy Mastic Hardener (CAS Mixture)			
Aquatic			
Crustacea	EC50	Daphnia	38.2855 mg/l, 48 hours estimated
Fish	LC50	Fish	21.7582 mg/l, 96 hours estimated
Components	Species		Test Results
2,2'-iminodi(ethylamine) (CAS 111-40-0)			
Aquatic			
Fish	LC50	Guppy (Poecilia reticulata)	1014 mg/l, 96 hours
BENZYL ALCOHOL (CAS 100-51-6)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	10.5 mg/l, 96 hours
Bisphenol A (CAS 80-05-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	9.2 - 11.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	3.6 - 5.4 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Biodegradability

Percent degradation (Aerobic biodegradation)

BENZYL ALCOHOL 94 %

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

BENZYL ALCOHOL 1.1

Bisphenol A 3.32

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methods

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

SCT

UN number UN2735

UN proper shipping name AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2,2'-iminodi(ethylamine))

Transport hazard class(es)

Class 8

Subsidiary risk -

Packing group I

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Bulk special provisions 274

DOT	
UN number	UN2735
UN proper shipping name	Amines, liquid, corrosive, n.o.s, or Polyamines, liquid, corrosive, n.o.s. (2,2'-iminodi(ethylamine))
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB3, T7, TP1, TP28
Packaging exceptions	154
Packaging non bulk	203
Packaging bulk	241
ADR	
UN number	UN2735
UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2,2'-iminodi(ethylamine))
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Hazard No. (ADR)	80
Tunnel restriction code	E
Packing group	III
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
RID	
UN number	UN2735
UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S (2,2'-iminodi(ethylamine))
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Packing group	III
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
ADN	
UN number	UN2735
UN proper shipping name	Amines, Liquid, Rosive, [or polyamines, liquid, corrosive, n.o.s.] (2,2'-iminodi(ethylamine))
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Packing group	III
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IATA	
UN number	UN2735
UN proper shipping name	Amines, liquid, corrosive, n.o.s. (2,2'-iminodi(ethylamine))
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	8L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN2735
UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2,2'-iminodi(ethylamine))
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-A, S-B
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

ADN; ADR; IATA; IMDG; RID; SCT

**DOT****15. Regulatory information****Safety, health and environmental regulations specific for the product in question**

This safety data sheet was prepared in accordance with the Official Mexican Standard (NOM-018-STPS-2000).

Mexico. Hazard identification guidance list (NOM-018-STPS)

ALCOHOL BENCILICO (HIDROXITOLUENO) (CAS 100-51-6)	Listed.
DIETILENTRIAMINA (CAS 111-40-0)	Listed.

Mexico. Substances subject to reporting for the pollutant release and transfer registry (PRTR)

Not listed.

International regulations**Montreal Protocol**

Not applicable.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information**List of abbreviations**

Not available.

Disclaimer

The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.